


## Raimond II

RAIMOND PUTS



The Raimond lights: perfect spheres of mathematical ingredients punctuated by tiny LED lights. Designer Raimond Puts was not only intrigued by the shape of the geodesic dome, but also with the mystery of prime numbers. It's no coincidence that the dimension of all Raimond lights resemble a prime number. The result of mathematical perfection, that brings the starry night sky into your home. Compatible with our Wireless Wall Switch, for quick and easy dimming that gives you full control over the light output.

---

### *Detailing*



Two steel spheres, interconnected with LEDs, form a thin and openwork triangular mesh that transport the electric current.

---

### *Colours*



Stainless steel

# Raimond II / Raimond II, R43

## Dimensions

43cm | 16.9"



## Product

**WIDTH** 43cm | 16.9"

**HEIGHT** 43cm | 16.9"

**DEPTH** 43cm | 16.9"

**DIAMETER** 43cm | 16.9"

**WEIGHT NETTO** 1.5kg | 3.31lbs

## Packaging

**WIDTH** 52cm | 20.5"

**HEIGHT** 60cm | 23.6"

**CUBAGE** 0.16m<sup>3</sup> | 5.73ft<sup>3</sup>

**LENGTH** 52cm | 20.5"

**WEIGHT** 5kg | 11.02lbs

## Technical cULus / CE

### ADDITIONAL

Compatible with our Wireless Wall Switch, for quick and easy dimming that gives you full control over the light output.

### MATERIAL

Stainless Steel Sphere with PMMA lenses

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE INCLUDED

Yes

### INPUT VOLTAGE

120-250

### MAX POWER CONSUMPTION

17W

### LIFETIME

50000 hours

### CABLE LENGTH

250cm | 98.4"; 1000cm | 393.7"

### COLOUR TEMPERATURE

2500 K

### LIGHT DIRECTION

All directions

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

92

### FREQUENCY

50/60

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Transparent with tinned cores

### CANOPY

Pebble III Steel Coated, ABS

### CRI

92

### LIGHT OUTPUT

664 lm

**DIMMING & LIGHTING CONTROL**

DALI dt6, Push / Pulse dim on mains, Wireless Wall Switch

See last page for more information about the dimming possibilities.



## Raimond II / Raimond II, R61

### Dimensions

61cm | 24"



### Product

**WIDTH** 61cm | 24"  
**HEIGHT** 61cm | 24"  
**DEPTH** 61cm | 24"  
**DIAMETER** 61cm | 24"  
**WEIGHT NETTO** 2kg | 4.41lbs

### Packaging

**WIDTH** 72cm | 28.3"  
**HEIGHT** 73cm | 28.7"  
**CUBAGE** 0.38m<sup>3</sup> | 13.36ft<sup>3</sup>  
**LENGTH** 72cm | 28.3"  
**WEIGHT** 8kg | 17.64lbs

### Technical cULus / CE

**ADDITIONAL**

Compatible with our Wireless Wall Switch, for quick and easy dimming that gives you full control over the light output.

**MATERIAL**

Stainless Steel Sphere with PMMA lenses

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

162

**INPUT VOLTAGE**

120-250

**FREQUENCY**

50/60

**MAX POWER CONSUMPTION**

26W

**LAMPHOLDER**

LED (Solid state)

**LIFETIME**

50000 hours

**CABLE COLOUR**

Transparent with tinned cores

**CABLE LENGTH**

250cm | 98.4"; 1000cm | 393.7"

**CANOPY**

Pebble III Steel Coated, ABS

**COLOUR TEMPERATURE**

2500 K

**CRI**

92

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

1134 lm

**DIMMING & LIGHTING CONTROL**


DALI dt6, Push / Pulse dim on mains, Wireless Wall Switch

*See last page for more information about the dimming possibilities.*

## Raimond II / Raimond II, R89

### Dimensions

89cm | 35"



### Product

**WIDTH** 89cm | 35"**HEIGHT** 89cm | 35"**DEPTH** 89cm | 35"**DIAMETER** 89cm | 35"**WEIGHT NETTO** 2.5kg | 5.51lbs

### Packaging

**WIDTH** 103cm | 40.6"**HEIGHT** 105cm | 41.3"**CUBAGE** 1.11m<sup>3</sup> | 39.34ft<sup>3</sup>**LENGTH** 103cm | 40.6"**WEIGHT** 14kg | 30.86lbs

### Technical cULus / CE

**ADDITIONAL**

Compatible with our Wireless Wall Switch, for quick and easy dimming that gives you full control over the light output.

**MATERIAL**

Stainless Steel Sphere with PMMA lenses

**ENERGY LABEL**

Energy Label B

**LIGHTSOURCE TYPE**

LED

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

252

**INPUT VOLTAGE**

120-250

**FREQUENCY**

50/60

**MAX POWER CONSUMPTION**

40W

**LAMPHOLDER**

LED (Solid state)

**LIFETIME**

50000 hours

**CABLE LENGTH**

250cm | 98.4"; 1000cm | 393.7"

**COLOUR TEMPERATURE**

2500 K

**LIGHT DIRECTION**

All directions

**DIMMING & LIGHTING CONTROL**

DALI dt6, Push / Pulse dim on mains, Wireless Wall Switch

*See last page for more information about the dimming possibilities.*

**CABLE COLOUR**

Transparent with tinned cores

**CANOPY**

Pebble III Steel Coated, ABS

**CRI**

92

**LIGHT OUTPUT**

1744 lm



## *Dimming & Lighting Control*

### *DALI dt6*

The luminaire is dimmable by integrating it into a DALI network. This is an universal and professional standard in home automation systems with endless control possibilities and ease. We advise to hire a professional to integrate the luminaire into your DALI network.

Compatible models: Raimond II, R43 cULus, Raimond II, R43 CE, Raimond II, R61 cULus, Raimond II, R61 CE, Raimond II, R89 cULus, Raimond II, R89 CE

---

### *Push / Pulse dim on mains*

The luminaire is dimmable by using an external momentary switch or pushbutton switch. The switch is usually mounted on an existing wall socket. In some cases a Phase or Control wire needs to be added to your home's wiring. The switch should be suitable for Mains Voltage and of the type 'normal off - momentary on'. The luminaire dims perfectly when the switch makes and holds contact. A short press switches between on and off.

Compatible models: Raimond II, R43 cULus, Raimond II, R43 CE, Raimond II, R61 cULus, Raimond II, R61 CE, Raimond II, R89 cULus, Raimond II, R89 CE

---

### *Wireless Wall Switch*

With our Wireless Wall Switch, you'll have full control over your Moooi lighting design with one touch. Our Wireless Wall Switch comprises two components, a wall switch and radio device to put in the canopy of your Moooi lighting design. The wall switch can be integrated in System 55 or Decora style wall switches. The Wireless Wall Switch communicates via Bluetooth with the radio device in the luminaires canopy. Within moments you can enjoy full and fluent dimming, all the way to dark.

Compatible models: Raimond II, R43 cULus, Raimond II, R43 CE, Raimond II, R61 cULus, Raimond II, R61 CE, Raimond II, R89 cULus, Raimond II, R89 CE

---