

## NR2

BERTJAN POT




NR2 by Bertjan Pot is an elegant and bright bubble of white or black thread. The lattice pattern creates a fine web that shines and glimmers in the light. The fine web is oval-shaped and bears the signature style of Bertjan Pot; designs created from an experiment with different materials. The integrated LED lamp in NR2 subtly diffuses a soft and magical glow around the room. NR2 is available in two different colours and sizes.

### *Detailing*




NR2's lattice patterned web of clean lines falls into place in any modern interior and brings an element of calmness in a maximalist's home.

### *Colours*



Just Black



White




Black

# NR2 / Large

## Dimensions

Ø75cm | 29.5"



## Product

**WIDTH** 75cm | 29.5"

**HEIGHT** 53cm | 20.9"

**DEPTH** 75cm | 29.5"

**DIAMETER** 75cm | 29.5"

**WEIGHT NETTO** 1.2kg | 2.65lbs

## Packaging

**WIDTH** 78cm | 30.7"

**HEIGHT** 69cm | 27.2"

**CUBAGE** 0.42m<sup>3</sup> | 14.82ft<sup>3</sup>

**LENGTH** 78cm | 30.7"

**WEIGHT** 8kg | 17.64lbs

## Technical CE

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

1

### INPUT VOLTAGE

120-277

### MAX POWER CONSUMPTION

26W

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Black

### CANOPY

Pebble II Black, ABS

### CHROM Y

0.41

### CRI

81

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE INCLUDED

Yes

### SHAPE

Oval

### FREQUENCY

50/60

### DIMMABLE

Yes

### LIFETIME

50000 hours

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CHROM X

0.48

### COLOUR TEMPERATURE

2468 K

### LIGHT DIRECTION

All directions

**LIGHT OUTPUT**

1047 lm



---

*Technical cULus***MATERIAL**

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

**ENERGY LABEL**

Energy Label B

**INSTALLATION REQUIRED**

Yes

**LIGHTSOURCE TYPE**

LED

**LIGHTSOURCE INCLUDED**

Yes

**NUMBER OF LIGHTSOURCES**

1

**SHAPE**

Oval

**INPUT VOLTAGE**

120-277

**FREQUENCY**

50-60

**MAX POWER CONSUMPTION**

26W

**DIMMABLE**

Yes

**LAMPHOLDER**

LED (Solid state)

**LIFETIME**

50000 hours

**CABLE COLOUR**

Black

**CABLE LENGTH**

400cm | 157.5"; 1000cm | 393.7"

**CANOPY**

Pebble II Black, ABS

**CHROM X**

0.48

**CHROM Y**

0.41

**COLOUR TEMPERATURE**

2468 K

**CRI**

81

**LIGHT DIRECTION**

All directions

**LIGHT OUTPUT**

1047 lm



# NR2 / Medium

## Dimensions

55cm | 21.7"



40cm | 15.7"

## Product

**WIDTH** 55cm | 21.7"

**HEIGHT** 40cm | 15.7"

**DEPTH** 55cm | 21.7"

**DIAMETER** 55cm | 21.7"

**WEIGHT NETTO** 0.9kg | 1.98lbs

## Packaging

**WIDTH** 57cm | 22.4"

**HEIGHT** 52cm | 20.5"

**CUBAGE** 0.17m<sup>3</sup> | 5.97ft<sup>3</sup>

**LENGTH** 57cm | 22.4"

**WEIGHT** 3.7kg | 8.16lbs

## Technical CE

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

Energy Label B

### LIGHTSOURCE TYPE

LED

### NUMBER OF LIGHTSOURCES

1

### INPUT VOLTAGE

208-277

### MAX POWER CONSUMPTION

12W

### LAMPHOLDER

LED (Solid state)

### CABLE COLOUR

Black

### CANOPY

Pebble II Black, ABS

### CRI

82

### LIGHT OUTPUT

450 lm

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE INCLUDED

Yes

### SHAPE

Oval

### FREQUENCY

50/60

### DIMMABLE

Yes

### LIFETIME

50000 hours

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### COLOUR TEMPERATURE

2700 K

### LIGHT DIRECTION

All directions



---

## Technical cULus

### MATERIAL

Ellipsoid from fiberglass with epoxy resin, ABS cover, PC diffuser and aluminum heatsink

### ENERGY LABEL

Energy Label B

### INSTALLATION REQUIRED

Yes

### LIGHTSOURCE TYPE

LED

### LIGHTSOURCE INCLUDED

Yes

### NUMBER OF LIGHTSOURCES

1

### SHAPE

Oval

### INPUT VOLTAGE

120

### FREQUENCY

50/60

### MAX POWER CONSUMPTION

12W

### DIMMABLE

Yes

### LAMPHOLDER

LED (Solid state)

### LIFETIME

50000 hours

### CABLE COLOUR

Black

### CABLE LENGTH

400cm | 157.5"; 1000cm | 393.7"

### CANOPY

Pebble II Black, ABS

### COLOUR TEMPERATURE

2700 K

### CRI

82

### LIGHT DIRECTION

All directions

### LIGHT OUTPUT

450 lm



---

## Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.

### DIMMER TYPE

Mains dimmable (trailing edge / reverse phase)

### LOAD TYPE

Capacitive load (C-Type)

---