



Materials	aluminium disc lined with flying leaf
Light source	halogen bi-pin bulb 12V GY6,35 / max 90W, included 60W / energy class B / lumen 1650 / K 3000 / CRI 100
Power supply	220-240V dimmable Triac / IGBT ?(110V available on request dimmable Triac only)
Dimensions	<div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">  </div> <div> <p>wall base Ø 16x6 cm, ledge 10 cm ca disc Ø 80 cm with flex Ø 1,5 x 80 cm, disc Ø 120 cm with flex Ø 1,5 x 100 cm,</p> </div> </div> <div style="margin-top: 10px;"> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;">  </div> <div> <p>ceiling base Ø 16x6 cm, ledge 10 cm ca disc Ø 80 cm with flex Ø 1,3 x 50 cm, disc Ø 120 cm with flex Ø 1,3 x 100 cm</p> </div> </div> </div>

Order code wall

LUP80	Ø 80 cm / gold
?	Ø 80 cm / silver
LUP80AG	
?LUP80R	Ø 80 cm / copper?
LUP	Ø 120 cm / gold
?LUPAG	Ø 120 cm / silver ?
LUPR	Ø 120 cm / copper

Order code ceiling

LUP80S	Ø 80 cm / gold
?	Ø 80 cm / silver
LUP80SAG	
?LUP80SR	Ø 80 cm / copper?
LUPS	Ø 120 cm / gold
?LUPSAG	Ø 120 cm / silver ?
LUPSR	Ø 120 cm / copper
